



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon-produktion.de
<http://www.chamaeleon-produktion.de>

TECHNICAL DATA SHEET

LASER Perfect Cut Liquid Compound

Product Description

LASER Perfect Cut Liquid Compound is a cutting compound suitable for both wool and foam application. Perfect Cut Liquid Compound works well on both high solids and medium solids paint systems.

Product Information

Size	Product Code	Carton Quantity
1kg	49901	6 pcs
0,5kg	49911	12 pcs

Applications

Use with foam and wool applicators

Characteristics

- Water based
- Silicone free
- Suitable for foam or wool application
- Ready to use.
- Dry use

Physical Properties

State	Liquid
Colour	Off White
Relative Density	1.34
Viscosity	40,000cps
Flash Point	>93°C
pH	9-11
VOC Content g/l	Refer to SDS

*For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: info@chamaeleon-produktion.de
See information on safety in Safety Data Sheet.*



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon-produktion.de
<http://www.chamaeleon-produktion.de>

Storage & Handling

Store at room temperature
Protect from frost
Shake container prior to use

Directions For Use

Step 1: Compounding

1. After wiping the panel with a suitable degreaser, fit the foam or wool applicator to a polishing machine.
2. Apply a small amount of LASER Perfect Cut Compound to the paint surface and spread uniformly over the surface using the Compounding applicator before starting the machine to reduce splatter.
3. Begin compounding with a free running speed of 1500 – 1800 rpm the applicator initially held at a slight angle (15°). Compound until marks have been removed, and finish with the foam held flat on the surface. For wool higher machine speeds can be used if desired, polish at a slight angle (15°). Compound until marks have been removed, and finish with the wool held flat on the surface.

Step 2: Finishing

Add more Perfect Cut Compound if necessary and repeat the procedure until all the marks are removed and a satisfactory gloss is achieved.
A third polishing step maybe desired, Perfect Shine Perfect finish can be used depending on the desired result.

To finish, wipe carefully with a Finishing Cloth

Additional Information

Professional users may refer to the Safety Data Sheet for this product.

*For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: info@chamaeleon-produktion.de
See information on safety in Safety Data Sheet.*